

## Psych 156A/ Ling 150: Acquisition of Language II

### Lecture 10 Grammatical Categories

### Announcements

HW2 due 5/15/12

- Remember that working in groups can be very helpful!

Please pick up HW1 if you have not yet done so

Review questions for grammatical categorization available

### Computational Problem

Identify classes of words that behave similarly (are used in similar syntactic environments). These are grammatical categories. If you know the grammatical category of the word, then you will know how this word is used in the language. This will allow you to recognize other words that belong to the same category since they will be used the same way.

"This is a DAX."



DAX = noun

Other nouns = bear, toy, teddy,  
stuffed animal, really great toy  
that I love so much,...

### Grammatical Categorization

Identify classes of words that behave similarly (are used in similar syntactic environments). These are grammatical categories. If you know the grammatical category of the word, then you will know how this word is used in the language. This will allow you to recognize other words that belong to the same category since they will be used the same way.

Examples of different categories in English:

noun = goblin, kitten, king, girl

Examples of how nouns are used:

I like that goblin. Kittens are adorable.

A king said that no girls would ever solve the Labyrinth.

### Grammatical Categorization

Identify classes of words that behave similarly (are used in similar syntactic environments). These are grammatical categories. If you know the grammatical category of the word, then you will know how this word is used in the language. This will allow you to recognize other words that belong to the same category since they will be used the same way.

Examples of different categories in English:  
verb = like, are, said, solve, stand

Examples of how verbs are used:  
I like that goblin. Kittens are adorable.  
A king said that no girls would ever solve the Labyrinth.  
Sarah was standing very close to him.

### Grammatical Categorization

Identify classes of words that behave similarly (are used in similar syntactic environments). These are grammatical categories. If you know the grammatical category of the word, then you will know how this word is used in the language. This will allow you to recognize other words that belong to the same category since they will be used the same way.

Examples of different categories in English:  
adjective = silly, adorable, brave, close

Examples of how adjectives are used:  
I like the silliest goblin. Kittens are so adorable.  
The king said that only brave girls would solve the Labyrinth.  
Sarah was standing very close to him.

### Grammatical Categorization


Identify classes of words that behave similarly (are used in similar syntactic environments). These are grammatical categories. If you know the grammatical category of the word, then you will know how this word is used in the language. This will allow you to recognize other words that belong to the same category since they will be used the same way.

Examples of different categories in English:  
preposition = near, through, to

Examples of how prepositions are used:  
I like the goblin near the king's throne.  
The king said that no girls would get through the Labyrinth.  
Sarah was standing very close to him.

### Grammatical Categorization

Identify classes of words that behave similarly (are used in similar syntactic environments). These are grammatical categories. If you know the grammatical category of the word, then you will know how this word is used in the language. This will allow you to recognize other words that belong to the same category since they will be used the same way.

"This is a DAX."		"He is SIBing."
DAX = ??		SIB = ??
"He is very BAV."		"He should sit GAR the other dax."
BAV = ??		GAR = ??

### Grammatical Categorization

Identify classes of words that behave similarly (are used in similar syntactic environments). These are grammatical categories. If you know the grammatical category of the word, then you will know how this word is used in the language. This will allow you to recognize other words that belong to the same category since they will be used the same way.

"This is a DAX."

DAX = noun



"He is SIBing."

SIB = verb

"He is very BAV."

BAV = adjective

"He should sit GAR the other dax."

GAR = preposition

### Categorization: How?

How might children initially learn what categories words are?

Idea 1: Deriving Categories from Semantic Information = Semantic Bootstrapping Hypothesis (Pinker 1984)

Children can initially determine a word's category by observing what kind of entity in the world it refers to.

### Categorization: How?

How might children initially learn what categories words are?

Idea 1: Deriving Categories from Semantic Information = Semantic Bootstrapping Hypothesis (Pinker 1984)

Children can initially determine a word's category by observing what kind of entity in the world it refers to.

objects, substance = noun  
(*goblins, glitter*)

action = verb  
(*steal, sing*)

property = adjective  
(*shiny, stinky*)



The word's meaning is then linked to innate grammatical category knowledge (nouns are objects/substances, verb are actions, adjectives are properties)

### Semantic Bootstrapping Hypothesis: Problem

Mapping rules are not perfect

Ex: not all action-like words are verbs

"bouncy", "a kick"  
action-like meaning, but they're not verbs



Ex: not all property-like words are adjectives

"they are shining brightly", "they glitter"  
seem to be referring to properties, but these aren't adjectives



### Categorization: How?

#### Idea 2: Distributional Learning

Children can initially determine a word's category by observing the linguistic environments in which words appear.

Kittens are adorable. Noun

Sarah was standing very close to him. Verb

I like the silliest goblin. Adjective

The king said that no girls would get through the Labyrinth. Preposition

### Are children sensitive to distributional information?

Children are sensitive to the distributional properties of their native language when they're born (Shi, Werker, & Morgan 1999).



15-16 month German infants can determine novel words are nouns, based on the distributional information around the novel words (Höhle et al. 2004)

18-month English infants can track distributional information like "*is...-ing*" to signal that a word is a verb (Santelmann & Jusczyk 1998)

### Mintz 2003: Is distributional information enough?

How do we know in child-directed speech (which is the linguistic data children encounter)...

- (1) What distributional information children should pay attention to?
- (2) If the available distributional information will actually correctly categorize words?

### Mintz 2003: What data should children pay attention to?

"...question is how the learner is to know *which* environments are important and which should be ignored. Distributional analyses that consider all the possible relations among words in a corpus of sentences would be computationally unmanageable at best, and impossible at worst."

One idea: local contexts

"...by showing that local contexts are informative, these findings suggested a solution to the problem of there being too many possible environments to keep track of: focusing on local contexts might be sufficient."

### Mintz 2003: Frequent Frames


Idea: What categorization information is available if children track frequent frames?

Frequent frame: X\_\_Y  
 where X and Y are words that frame another word and appear frequently in the child's linguistic environment

Examples:    the\_\_is                      can\_\_him  
                  the king is...            can trick him...  
                  the goblin is...           can help him...  
                  the girl is...                    can hug him...

### Mintz 2003: Samples of Child-Directed Speech

Data representing child's linguistic environment:  
 6 corpora of child-directed speech from the CHILDES database, which contains transcriptions of parents interacting with their children.



Corpus (sg.), corpora (pl). = a collection of data [from Latin *body*, a "body" of data]

### Mintz 2003: Defining "Frequent"

Definition of "frequent" for frequent frames:  
 Frames appearing a certain number of times in a corpus

"The principles guiding inclusion in the set of frequent frames were that frames should occur frequently enough to be noticeable, and that they should also occur enough to include a variety of intervening words to be categorized together.... a pilot analysis with a randomly chosen corpus, Peter, determined that the 45 most frequent frames satisfied these goals and provided good categorization."

Set of frequent frames = 45 most frequent frames

### Mintz 2003: Defining "Frequent"

Example of deciding which frames were frequent:

Frame	How often it occurred in the corpus
(1) the__is	600 times
(2) a__is	580 times
(3) she__it	450 times
...	
(45) they__him	200 times
(46) we__have	199 times
...	

These frames considered "frequent"

Mintz 2003:  
Testing the Categorization Ability of  
Frequent Frames

Try out frequent frames on a corpus of child-directed speech.

Frame (1): the \_\_\_ is

Transcript: "...the radio is in the way...but the doll is...and the teddy is..."

radio, doll, teddy are placed into the same category by the \_\_\_ is

Frame (13): you \_\_\_ it

Transcript: "...you draw it so that he can see it... you dropped it on purpose!...so he hit you with it..."

draw, dropped, with are placed into the same category by you \_\_\_ it

Mintz 2003:  
Determining the success of frequent frames

Precision =  $\frac{\# \text{ of words identified correctly as Category within frame}}{\# \text{ of words identified as Category within frame}}$

Recall =  $\frac{\# \text{ of words identified correctly as Category within frame}}{\# \text{ of words that should have been identified as Category}}$

Mintz 2003:  
Determining the success of frequent frames

Precision =  $\frac{\# \text{ of words identified correctly as Category within frame}}{\# \text{ of words identified as Category within frame}}$

Recall =  $\frac{\# \text{ of words identified correctly as Category within frame}}{\# \text{ of words that should have been identified as Category}}$

Frame: you \_\_\_ it

Category: draw, dropped, with (similar to Verb so compare to Verb)

# of words correctly identified as Verb = 2 (draw, dropped)

# of words identified as Verb = 3 (draw, dropped, with)

Precision for you \_\_\_ it = 2/3

Mintz 2003:  
Determining the success of frequent frames

Precision =  $\frac{\# \text{ of words identified correctly as Category within frame}}{\# \text{ of words identified as Category within frame}}$

Recall =  $\frac{\# \text{ of words identified correctly as Category within frame}}{\# \text{ of words that should have been identified as Category}}$

Frame: you \_\_\_ it

Category: draw, dropped, with (similar to Verb so compare to Verb)

# of words correctly identified as Verb = 2 (draw, dropped)

# of words should be identified as Verb = all verbs in corpus (play, sit, draw, dropped, ran, kicked, ...)

Mintz 2003:  
Determining the success of frequent frames

Precision =  $\frac{\text{\# of words identified correctly as Category within frame}}{\text{\# of words identified as Category within frame}}$

Recall =  $\frac{\text{\# of words identified correctly as Category within frame}}{\text{\# of words that should have been identified as Category}}$

Frame: you \_\_\_ it

Category: draw, dropped, with (similar to Verb so compare to Verb)

# of words correctly identified as Verb = 2

# of words should be identified as Verb = all verbs in language

Recall = 2/all (much smaller number)

Mintz 2003:  
Some actual frequent frame results

Frame: you \_\_\_ it

Category includes:

put, want, do, see, take, turn, taking, said, sure, lost, like, leave, got, find, throw, threw, think, sing, reach, picked, get, dropped, seen, lose, know, knocked, hold, help, had, gave, found, fit, enjoy, eat, chose, catch, with, wind, wear, use, took, told, throwing, stick, share, sang, roll, ride, recognize, reading, ran, pulled, pull, press, pouring, pick, on, need, move, manage, make, load, liked, lift, licking, let, left, hit, hear, give, flapped, fix, finished, drop, driving, done, did, cut, crashed, change, calling, bring, break, because, banged

Mintz 2003:  
Some actual frequent frame results

Frame: the \_\_\_ is

Category includes:

moon, sun, truck, smoke, kitty, fish, dog, baby, tray, radio, powder, paper, man, lock, lipstick, lamb, kangaroo, juice, ice, flower, elbow, egg, door, donkey, doggie, crumb, cord, clip, chicken, bug, brush, book, blanket, mommy

Mintz 2003:  
How successful frequent frames were

Precision: Above 90% for all corpora (high) = very good!


Interpretation: When a frequent frame clustered words together into category, they often did belong together. (Nouns were put together, verbs were put together, etc.)

Recall: Around 10% for all corpora (very low) = maybe not as good...

Interpretation: A frequent frame made lots of little clusters, rather than being able to cluster all the words into one category. (So, there were lots of Noun-ish clusters, lots of Verb-ish clusters, etc.)

**Mintz 2003:**  
How successful frequent frames were


Precision: Above 90% for all corpora (high) = very good!



Only a few errors within a cluster

Recall: Around 10% for all corpora (very low) = maybe not as good...

Lots of little clusters instead of one big cluster per category



**Mintz 2003:**  
Getting better recall

How could we form just one category of Verb, Noun, etc.?

Observation: Many frames overlap in the words they identify.

the__is dog cat king girl	the__was dog cat king teddy	a__is dog goblin king girl	that__is ... cat goblin king teddy
---------------------------------------	---	--	--

What about putting clusters together that have a certain number of words in common?

**Mintz 2003:**  
Getting better recall

How could we form just one category of Verb, Noun, etc.?

Observation: Many frames overlap in the words they identify.

the__is dog cat king girl	the__was dog cat king teddy	a__is dog goblin king girl	that__is ... cat goblin king teddy
---------------------------------------	---	--	--

**Mintz 2003:**  
Getting better recall

How could we form just one category of Verb, Noun, etc.?

Observation: Many frames overlap in the words they identify.

the__is, the__was dog cat king girl teddy	a__is dog goblin king girl	that__is ... cat goblin king teddy
--	--	--



### Mintz 2003: Getting better recall

How could we form just one category of Verb, Noun, etc.?

Observation: Many frames overlap in the words they identify.

the\_\_is/was  
dog  
cat  
king  
girl  
teddy

a\_\_is  
dog  
goblin  
king  
girl

that\_\_is ...  
cat  
goblin  
king  
teddy

### Mintz 2003: Getting better recall

How could we form just one category of Verb, Noun, etc.?

Observation: Many frames overlap in the words they identify.

the\_\_is/was, a\_\_is  
dog goblin  
cat  
king  
girl  
teddy

that\_\_is ...  
cat  
goblin  
king  
teddy

### Mintz 2003: Getting better recall

How could we form just one category of Verb, Noun, etc.?

Observation: Many frames overlap in the words they identify.

the/a\_\_is/was  
dog goblin  
cat  
king  
girl  
teddy

that\_\_is ...  
cat  
goblin  
king  
teddy

### Mintz 2003: Getting better recall

How could we form just one category of Verb, Noun, etc.?

Observation: Many frames overlap in the words they identify.

the/a/that\_\_is/was  
dog teddy  
cat goblin  
king  
girl

Recall goes up to 91% (very high) = very good!  
Precision stays above 90% (very high) = very good!

## Experimental support for frequent frames

"Another important difference...adults will categorize words in an artificial language based on their occurrence within frames... whereas bigram regularity alone has failed to produce categorization in artificial grammar experiments, without additional cues..." - Mintz 2003

Also, Mintz (2006) shows that 12-month-olds are sensitive to frequent frames in an experimental setup



## Cross-linguistic Application?

"The fundamental notion is that a relatively local context *defined by frequently co-occurring units* can reveal a target word's category...[here] the units were words and the frame contexts were defined by words that frequently co-occur. In other languages, a failure to find frequent word frames could trigger an analysis of co-occurrence patterns at a different level of granularity, for example, at the level of sub-lexical morphemes. The frequently co-occurring units in these languages are likely to be the inflectional morphemes which are limited in number and extremely frequent." – Mintz 2003

### Western Greenlandic

Alikusersullammasuaanerartassagaluarpaali.  
 aliku-sersu-i-lammas-sua-a-nerar-ta-ssa-galuar-paal-li  
 entertainment-provide-SEMTRANS-one.good.at-COP-say-that-REP-FUT-sure.but-3.PL.SUBJ/3SG.OBJ-but  
 'However, they will say that he is a great entertainer, but ...'

## Cross-linguistic Application?

Some work done for French (Chemla et al. 2009), Spanish (Weisleder & Waxman 2010), Chinese (Cai 2006, Xiao, Cai, & Lee 2006), German (Wang et al. 2010, Stumper et al. 2011), Turkish (Wang et al. 2010)

Very similar results: high precision, low recall (before aggregation)  
 -However, for Turkish and German, it's better to have FFs at the morpheme (rather than whole word) level

However, other work in Dutch (Erkelens 2008, Liebbrandt & Powers 2010) suggests that FFs don't fare as well, especially when they surround function words (like "the" and "a").

## Mintz 2003: Recap

Frequent frames are non-adjacent co-occurring words with one word in between them. (ex: the\_\_is)

They are likely to be information young children are able to track, based on experimental studies.

When tested on realistic child-directed speech, frequent frames do very well at grouping words into clusters which are very similar to actual grammatical categories like Noun and Verb.

Frequent frames could be a very good strategy for children to use when they try to learn the grammatical categories of words.

Wang & Mintz 2008:  
 Simulating children using frequent frames

"...the frequent frame analysis procedure proposed by Mintz (2003) was not intended as a model of acquisition, but rather as a demonstration of the information contained in frequent frames in child-directed speech...Mintz (2003) did not address the question of whether an actual learner could detect and use frequent frames to categorize words..."



Wang & Mintz 2008:  
 Simulating children using frequent frames

"This paper addresses this question with the investigation of a computational model of frequent frame detection that incorporates more psychologically plausible assumptions about the memor[y] resources of learners."

Computational model: a program that simulates the mental processes occurring in a child. This requires knowing what the input and output are, and then testing the algorithms that can take the given input and transform it into the desired output.

Considering Children's Limitations

Memory Considerations

- (1) Children possess limited memory and cognitive capacity and cannot track all the occurrences of all the frames in a corpus.
- (2) Memory retention is not perfect: infrequent frames may be forgotten.

The Model's Operation

- (1) Only 150 frame types (and their frequencies) are held in memory
- (2) Forgetting function: frames that have not been encountered recently are less likely to stay in memory than frames that have been recently encountered

Wang & Mintz (2008): How the model works

Child encounters an utterance (e.g. "You read the story to mommy.")

Child segments the utterance into frames:

	You	read	the	story	to	mommy.
(1)	you	X	the			
(2)		read	X	story		
(3)			the	X	to	
(4)				story	X	mommy

Frames:

you\_\_the, read\_\_story, the\_\_to, story\_\_mommy

### Wang & Mintz (2008): How the model works

In the beginning, there is nothing in the learner's memory.

Memory

Activation

Processing Step 1

### Wang & Mintz (2008): How the model works

If memory is not full, a newly-encountered frame is added to the memory and its initial activation is set to 1.

Memory  
you\_\_the

Activation  
1.0

Processing Step 1

### Wang & Mintz (2008): How the model works

The forgetting function is simulated by the activation for each frame in memory decreasing by 0.0075 after each processing step.

Memory  
you\_\_the

Activation  
0.9925

Forgetting function

### Wang & Mintz (2008): How the model works

When a new frame is encountered, the updating depends on whether the memory is already full or not. If it is not and the frame has not already been encountered, the new frame is added to the memory with activation 1.

Memory  
read\_\_story  
you\_\_the

Activation  
1.0  
0.9925

Processing Step 2 (read\_\_story)

Wang & Mintz (2008): How the model works

When a new frame is encountered, the updating depends on whether the memory is already full or not. If it is not and the frame has not already been encountered, the new frame is added to the memory with activation 1.

Memory	Activation
read__story	0.9925
you__the	0.9850

Forgetting function

Wang & Mintz (2008): How the model works

When a new frame is encountered, the updating depends on whether the memory is already full or not. If it is not and the frame has not already been encountered, the new frame is added to the memory with activation 1.

Memory	Activation
the__to	1.0
read__story	0.9925
you__the	0.9850

Processing step 3 (the\_\_to)

Wang & Mintz (2008): How the model works

When a new frame is encountered, the updating depends on whether the memory is already full or not. If it is not and the frame has not already been encountered, the new frame is added to the memory with activation 1.

Memory	Activation
the__to	0.9925
read__story	0.9850
you__the	0.9775

Forgetting function

Wang & Mintz (2008): How the model works

When a new frame is encountered, the updating depends on whether the memory is already full or not. If it is not and the frame has not already been encountered, the new frame is added to the memory with activation 1.

Memory	Activation
story__mommy	1.0
the__to	0.9925
read__story	0.9850
you__the	0.9775

Processing step 4 (story\_\_mommy)

Wang & Mintz (2008): How the model works

When a new frame is encountered, the updating depends on whether the memory is already full or not. If it is not and the frame has not already been encountered, the new frame is added to the memory with activation 1.

Memory	Activation
story__mommy	0.9925
the__to	0.9850
read__story	0.9775
you__the	0.9700

Forgetting function

Wang & Mintz (2008): How the model works

If the frame is already in memory because it was already encountered, activation for that frame increases by 1.

Memory	Activation
story__mommy	0.9925
the__to	0.9850
read__story	0.9775
you__the	0.9700

Processing step 5: (you\_\_the)

Wang & Mintz (2008): How the model works

If the frame is already in memory because it was already encountered, activation for that frame increases by 1.

Memory	Activation
story__mommy	0.9925
the__to	0.9850
read__story	0.9775
you__the	1.9700

Processing step 5: (you\_\_the)

Wang & Mintz (2008): How the model works

If the frame is already in memory because it was already encountered, activation for that frame increases by 1.

Memory	Activation
you__the	1.9700
story__mommy	0.9925
the__to	0.9850
read__story	0.9775

Processing step 5: (you\_\_the)

Wang & Mintz (2008): How the model works

If the frame is already in memory because it was already encountered, activation for that frame increases by 1.

Memory	Activation
you__the	1.9625
story__mommy	0.9850
the__to	0.9775
read__story	0.9700

Forgetting function

Wang & Mintz (2008): How the model works

Eventually, since the memory only holds 150 frames, the memory will become full.

Memory	Activation
story__mommy	4.6925
the__to	3.9850
read__story	3.9700
you__the	2.6925
...	...
she__him	0.9850
we__it	0.7500

Memory after processing step 200

Wang & Mintz (2008): How the model works

At this point, if a frame not already in memory is encountered, it replaces the frame with the least activation, as long as that activation is less than 1.0.

Memory	Activation
story__mommy	4.6925
the__to	3.9850
read__story	3.9700
you__the	2.6925
...	...
she__him	0.9850
we__it	0.7500

Processing step 201: because\_\_said

Wang & Mintz (2008): How the model works

At this point, if a frame not already in memory is encountered, it replaces the frame with the least activation, as long as that activation is less than 1.0.

Memory	Activation
story__mommy	4.6925
the__to	3.9850
read__story	3.9700
you__the	2.6925
...	...
she__him	0.9850
<del>we__it</del>	<del>0.7500</del>

Processing step 201: because\_\_said

Wang & Mintz (2008): How the model works

At this point, if a frame not already in memory is encountered, it replaces the frame with the least activation, as long as that activation is less than 1.

Memory	Activation
story__mommy	4.6925
the__to	3.9850
read__story	3.9700
you__the	2.6925
...	...
because__said	1.0000
she__him	0.9850

Processing step 201: because\_\_said

Wang & Mintz (2008): How the model works

Eventually, however, all the frames in memory will have been encountered often enough that their activations are greater than 1.

Memory	Activation
story__mommy	9.6925
the__to	8.9850
read__story	8.9700
you__the	5.6925
...	...
we__her	3.9700
she__him	2.9850

Memory after processing step 5000

Wang & Mintz (2008): How the model works

At this point, no change is made to memory since the new frame's activation of 1 would be less than the least active frame in memory.

Memory	Activation
story__mommy	9.6925
the__to	8.9850
read__story	8.9700
you__the	5.6925
...	...
we__her	3.9700
she__him	2.9850

Processing step 5001 (because\_\_him)

Wang & Mintz (2008): How the model works

The forgetting function is then invoked.

Memory	Activation
story__mommy	9.6850
the__to	8.9775
read__story	8.9625
you__the	5.6850
...	...
we__her	3.9625
she__him	2.9775

Forgetting function



### Wang & Mintz (2008): How the model did

Using same corpora for input as Mintz (2003)  
(6 from CHILDES: Anne, Aran, Even, Naomi, Nina, Peter)

The model's precision was above 0.93 for all six corpora.

This is very good!

When the model decided a word belonged in a particular category  
(Verb, Noun, etc.) it usually did.




Figure 1 Accuracies after processing the six corpora

### Wang & Mintz (2008): Conclusions

“...our model demonstrates very effective categorization of words. Even with limited and imperfect memory, the learning algorithm can identify highly informative contexts after processing a relatively small number of utterances, thus yield[ing] a high accuracy of word categorization. It also provides evidence that frames are a robust cue for categorizing words.”

### Wang & Mintz (2008): Recap

While Mintz (2003) showed that frequent frame information is useful for categorization, it did not demonstrate that children - who have constraints like limited memory and less cognitive processing power than adults - would be able to effectively use this information.

Wang & Mintz (2008) showed that a model using frequent frames in a psychologically plausible way (that is, a way that children might identify and use frequent frames) was able to have the same success at identifying the grammatical category that a word is.

### Questions?



Use this time to work on HW2 and the review questions.